

CONFIDENTIAL



UNIVERSITI TUN HUSSEIN ONN MALAYSIA

**FINAL EXAMINATION
SEMESTER 2
SESSION 2016/2017**

COURSE NAME : TRIBOLOGY
COURSE CODE : BDC 40503
PROGRAMME : BDD
EXAMINATION DATE : JUN 2017
DURATION : 3 HOURS
**INSTRUCTION : PART A: ANSWER ALL
QUESTIONS
PART B: ANSWER ONE (1) OUT
OF TWO QUESTIONS ONLY**

THIS QUESTION PAPER CONSISTS OF NINE (9) PAGES

CONFIDENTIAL

CONFIDENTIAL

BDC 40503

PART A: ANSWER ALL QUESTIONS

Q1 (a) Describe the meaning of the following terminologies:

- (i) Newtonian fluid
- (ii) Fretting wear
- (iii) Viscosity Index
- (iv) Average roughness
- (v) Elastohydrodynamic lubrication

(5 marks)

(b) Hip implant experience tribological associated issues which require revision surgery of the implant. Discuss on the possible tribological mechanisms associated with the implant.

(5 marks)

(c) The Stribeck curve shows how the boundary, mixed, and hydrodynamic lubrication are divided. Describe the curve with graphics illustration.

(5 marks)

(d) By understanding the principle of Reynolds equation, discuss the significance of each terms in the equation.

$$\frac{\partial}{\partial x} \left[\frac{\rho h^3}{\eta} \frac{\partial p}{\partial x} \right] + \frac{\partial}{\partial y} \left[\frac{\rho h^3}{\eta} \frac{\partial p}{\partial y} \right] = 6 \left[\frac{\partial}{\partial x} \{ \rho h (U_1 + U_2) \} + \frac{\partial}{\partial y} [\rho h \{ V_1 + V_2 \}] + \dots + \frac{2d}{dt} (\rho h) \right]$$

(5 marks)

CONFIDENTIAL

BDC 40503

Q2 Roller with 2 mm radius and 5 mm length is coated with Diamond Like Coating (DLC) and rolls without sliding with a speed of 60 rpm on a DLC coated flat surface. Water with viscosity of 0.00025 Pas is used as intervening fluid. Load of 2 mN is applied. The composite roughness of the surface is 100 nm. Modulus of elasticity for DLC is 800 GPa with Poisson's ratio of 0.2 and take its shear strength to be 100 MPa. The water meniscus force, F_m for DLC is 5×10^{-4} mN. If the average asperity tip radius is 1 μm , and assume 1,000 such asperity-pairs in the contact area.

(a) Assess the effectiveness of water as lubricant.

(10 marks)

(b) Determine the adhesive coefficient of friction.

(10 marks)

CONFIDENTIAL

BDC 40503

Q3 A semi-automated assembly machine, assembles and welds aerospace components for a single shift of 7.5 hours, 5 days a week, planned throughput is 250 units/hour; actual output = 3875 units/week.

The following losses are encountered during assembly:

- Incorrect assembly causes the machine to stop and needs re-set on average 5 times/hr. where 1 unit and 2 minutes are lost. (This leads to performance loss due to minor stoppage and also quality loss.
- Worn out electrodes are to be replaced once per week, it takes 1 hour when 30 units are scrapped.
- Burst out cooling hose causes a machine breakdown once in a month and replacement takes 5 hours.
- Misaligned fixture causes a loss of 220 units/ week.
- For different size parts, fixtures to be removed and replaced and electrode position to be adjusted 3 times/week which takes 2.25 hours where 24 units are scrapped each time.
- Actuating cylinder sometimes sticks for 30 minutes/day causing production delay which takes double cycle time.
- Application of rust protective spray by operator stopping the machine at the start and end of the day takes 5 minutes each time.
- Limit switches corrode once in every 6 weeks stopping the machine and replacement takes 6 hours.

Evaluate the overall equipment effectiveness.

(20 marks)

CONFIDENTIAL

BDC 40503

Q4 An instantaneous contact of a pair of spur gear teeth is represented by a rigid roller of 5 mm radius and length 10 mm against a semi-infinite elastic half space of equivalent elastic modulus E^* . The sliding speed of the gear teeth is 1 m/s and the lubricant entrainment speed is 0.5 m/s. This gear is running under load of 600 N. The lubricant viscosity at atmospheric pressure is 0.07 Pas and the pressure viscosity coefficient is 10^{-8} Pa^{-1} . Both gears are made of heat treated steel of Young's modulus of elasticity 210 GPa, and Poisson's ratio 0.3 (assume elastic line contact with maximum Hertzian pressure distribution and isothermal conditions).

(a) Calculate the footprint area of contact of these two gears

(4 marks)

(b) By assessing the lubricant's thickness and viscosity, evaluate the coefficient of friction of the gear.

(16 marks)

CONFIDENTIAL

BDC 40503

PART B: ANSWER ONE (1) OUT OF TWO QUESTIONS ONLY

Q5 A turbine engine is running at 3000 rev/min, under radial load of 200 kN. The dimension of the journal bearing is 20 cm in diameter, and 10 cm in length. The oil supply temperature is 40 °C with density of 850 kg/m³ at maximum pump pressure of 9×10^5 N/m². The coefficient of specific heat of lubricant is 1880 J/kg°C and the constant of heat removal k_r is 0.75. The minimum oil film thickness, h_o must not be less than 20 microns meter due to surface finish constraint. The oil temperature-viscosity relation is given by $\eta = 0.1597 \exp^{[700.81/(t-203.1)]}$.

(a) Calculate the radial clearance of the journal for the case of eccentricity ratio value of 0.4.

(3 marks)

(b) Calculate the increase of the lubricant temperature given that the flow rate constant is 0.751 and friction constant is 17.1 with reciprocal Sommerfeld number is 0.7855.

(4 marks)

(c) Determine the lubricant viscosity under this situation.

(5 marks)

(d) Determine the effective temperature using the lubricant's temperature-viscosity relation.

(3 marks)

(e) Discuss on the subsequent steps to design a journal bearing for this application.

(5 marks)

CONFIDENTIAL

BDC 40503

Q6 A circular hydrostatic central orifice step bearing supports the end of a 0.04 m diameter shaft under purely axial load. The outside diameter of the bearing is 0.04 m and its recess diameter is 0.02 m. From a constant pump supply pressure of 10 MN/m², an oil of viscosity 25 cP is fed, via a capillary tube, to a pressure in the recess of 5 MN/m²; the bearing film thickness is to be 10⁻⁴ m. (assume $L/d = 100$ is sufficient to maintain purely viscous flow).

- (a) Determine the load capacity of the bearing. (3 marks)
- (b) Calculate the flow of lubricant. (4 marks)
- (c) Determine the stiffness of the bearing. (5 marks)
- (d) Determine the lifting power of the bearing. (3 marks)
- (e) Design suitable capillary tube dimension if viscous flow is to be maintained within it. (5 marks)

- END OF QUESTIONS -

CONFIDENTIAL

BDC 40503

FINAL EXAMINATION

SEMESTER/SESSION : SEM 2/2016/2017
 COURSE NAME : TRIBOLOGY

PROGRAMME : BDD
 COURSE CODE: BDC 40503

USEFUL FORMULAS

$$U = 2\pi RN$$

$$h_o = \frac{4LU\eta_o R}{W}$$

$$\lambda = \frac{h}{\sigma}$$

$$F_n = F_m + W$$

$$F_a = A\tau_s$$

$$A = 3.2 \frac{F_n}{E^*} \sqrt{\frac{r}{\sigma_p}}$$

$$\mu = \frac{F_a}{F_n}$$

$$\frac{1}{E^*} = \frac{1 - \nu_1^2}{E_1} + \frac{1 - \nu_2^2}{E_2}$$

$$a = \left(\frac{4WR}{\pi LE^*} \right)^{\frac{1}{2}}$$

$$\frac{h_o}{R} = 2.076 \left(\frac{\alpha \eta_o V}{R} \right)^{\frac{8}{11}} \left(\frac{E^* R}{P'} \right)^{\frac{1}{11}}$$

$$Z = \frac{\alpha}{(5.1 \times 10^{-9}) [\ln(\eta_o) + 9.67]}$$

$$p_o = \left(\frac{WE^*}{\pi LR} \right)^{\frac{1}{2}}$$

$$\eta = \eta_o \left(\frac{63 \times 10^{-6}}{\eta_o} \right)^{1 - \left\{ 1 + \frac{p_o}{196 \times 10^6} \right\}^z}$$

$$\tau = \left(\frac{\eta U}{h_o} \right)$$

$$F_a = A\tau_s$$

$$\mu = \frac{F}{W}$$

CONFIDENTIAL

BDC 40503

FINAL EXAMINATION

SEMESTER/SESSION : SEM 2 / 2016/2017
 COURSE NAME : TRIBOLOGY

PROGRAMME : BDD
 COURSE CODE : BDC 40503

$$c = \frac{h_o}{(1 - \varepsilon)}, c = \frac{h_1}{(1 + \varepsilon)}$$

$$K_1 = \frac{k_1}{\rho c_p}$$

$$\Delta\theta_s = \frac{2\mu^* K_1 W}{Q^* R L}$$

$$\eta = \frac{1}{S} \left(\frac{W}{\pi N D L} \right) \left(\frac{c}{R} \right)^2$$

$$A = \pi R^2$$

$$\bar{A} = \frac{1}{2} \left(\frac{1 - 1/\bar{R}^2}{\ln(\bar{R})} \right)$$

$$\bar{R} = R/R_o$$

$$\bar{B} = \frac{R}{6 \ln \left(\frac{R}{R_o} \right)}$$

$$W = A p_r \bar{A}$$

$$Q = \frac{p_r h^3}{\eta} \bar{B}$$

$$W = \frac{A p_s \bar{A}}{h^3 K_c \bar{B} + 1}$$

$$\lambda_c = \frac{3W}{h} \left(\frac{1}{1 + (1/\bar{B} K_c h^3)} \right)$$

$$P = Q p_r$$

$$K_c = \frac{128 L_c}{\pi d^4}$$

Availability (A) = { (loading time) – (down time) } / loading time

Performance rate (P) = { Quantity produced } / { Time run x Capacity / Given time }

Quality (Q) = { Amount produced – defects – reprocess } / Amount produced

Overall equipment effectiveness (OEE) = (A)(P)(Q)
